



Construction Grade Dual Deck Rough Terrain Scissor Lifts

Model
5492RT


- Up to 60 ft. (18.5m) working height
- Ultra Deck with slide-out extension deck(s) and incremental locking positions
- Quad-Trax 4wd power package
- Fully proportional drive and lift controls
- Outrigger support for platform stability on heavy duty job sites with "one-touch" auto leveling
- Oscillating rear axle with 14" (35.6 cm) ground clearance
- Easy maintenance access with pull-out engine and hydraulic modules
- Non-skid metal deck construction
- No-maintenance scissor bearings
- Large sheet loading entrances (fore and aft)



The largest scissor lift made in North America!



Ultra-deck...



Ultra-speed...



...and Ultra-gradeability.



Features

Work Area

Ultra Deck includes single roll-out deck extension with incremental locking positions as standard equipment

Dual Deck Option - Includes a second roll-out deck extension with incremental locking positions

Easy access dual side entrances

Non-skid metal deck construction

Large sheet loading entrances (fore and aft) accommodate 48" (1.22 m) material

110V Power to Platform

Combination of wide beams and large pins in maintenance-free bearings for larger load bearing surface in scissor pivot areas

Performance

Fully Proportional Drive and Lift Controls

Oscillating rear axle with 14" (35.6 cm) ground clearance

High Torque Power Package

Auto-Leveling Outriggers

Engine/Power

Kubota Dual Fuel Engine (Gasoline/Liquid Propane)

Serviceability

Maintenance-free Scissor Bearings

Easy maintenance access to mechanical and electrical components with pullout engine/hydraulic module

Logically grouped components and numbered wiring for easy reference

Safety

Dedicated compartments protect electrical and hydraulic components

Emergency shut-off at platform and lower controls

Non-Skid Metal Deck Construction

Motion Alarm

Drive Speed Interlock

Multi-Axis Tilt Sensor

Multiple Disc Brakes, manual brake release

Scissor Maintenance Lock

Other Features

Platform Swing Gates

Fold-Down Guardrails

Hour Meter

Powder Coat Finish

Machine Tie Downs

Foam Filled Tires

Optional Features

Ultra Deck with Dual Extension Decks

Platform Work Lights

Lanyard Attachments (6)

120V 2250W Generator

Flashing Beacon (continuous)

Non-Marking RT Tires (foam-filled)

Automotive Horn

High Floatation Tires (foam-filled)

Removable Upper Controls

Kubota Turbo-Charged Diesel Engine

Air Line to Platform

CE Compliant Options

All Motion Alarm

Australian Compliant Options

Quad-Trax 4wd Power Pkg.

CSA compliant Options

1 or 2 year Extended Warranty

Model	5492RT	
	U.S.	Metric
Heights		
Working Height*	60 ft.*	18.5 m*
Platform Height	54 ft.	16.5 m
Maximum Drive Height	30 ft.	9.14 m
Platform Deck Height (Stowed)	6 ft. 7.5 in.	2.02 m
Stowed Height (Top Guardrail)	10 ft. 4 in.	3.15 m
Stowed Height (Rails Lowered)	7 ft. 10 in.	2.38 m
Ground Clearance	14 in.	35.6 cm
Dimensions		
Width	92 in.	2.34 m
Platform Length, Deck(s) Stowed:		
w/ Single Deck Extension	17 ft. 2 in.	5.23 m
w/ Optional Dual Deck Extensions	17 ft. 5 in.	5.3 m
Platform Length, Deck(s) Extended:		
w/ Single Deck Extension	20 ft. 10 in.	6.35 m
w/ Optional Dual Deck Extensions	24 ft. 9 in.	7.54 m
Outside Platform Width	75 in.	1.9 m
Wheel base	113 in.	2.87 m
Lift Capacity	1,500 lbs.	680 kg
Roll-Out Deck Capacity (per deck)	500 lbs.	227 kg
Speeds		
Raise/Lower Speed	55/49 sec.	
Drive Speed (Stowed)	4.5 mph	7.2 km/h
Drive Speed (Raised)	0.4 mph	.6 km/h
Performance		
Gradeability	45%	
Turning Radius (Inside - 2W Steer)	6 ft. 10 in.	2.08 m
Turning Radius (Outside - 2W Steer)	17 ft. 5 in.	5.3 m
Weight **	19,500 lbs.**	8845 kg
Brakes	Multi-Disc	
Power Source	Kubota Dual Fuel Engine (Gasoline/Liquid Propane)	
Controls	Proportional Lift and Drive	
Drive	Planetary drive/two-speed wheel motors	
Hydraulics	Variable Displacement	
Axle Oscillation	Rear Axle	
Tires	12 x 33 in. (30 x 84 cm)	
Fuel Tank Capacity	30 gal.	113.6 L
Hydraulic Fluid Capacity	30 gal.	113.6 L

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006, CSA B354.2-01, AS 1418.10 and CE Compliance as applicable. Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:



MEC Australia

Unit 4 18-20 Prospect Place, Berrinba, Queensland, Australia, 4117

PO Box 1792 Sunnybank Hills, Queensland, Australia, 4109

P: 07 3808 8826 / F: 07 3808 8025

E: admin@mecaustalia.com.au

W: www.mecaustalia.com.au