

Dingli 
Australia

www.dingliaustralia.com.au




E-Tech

S06-E

ELECTRIC SCISSOR LIFTS

E-Tech

S06-E



S.W.L	230kg/507lb
S.W.L on extension	113kg/249lb
Maximum workers number	2 Indoor/1 Outdoor



Working height	7.8m/25ft7in
Platform floor height	5.8m/19ft



Overall length	1.86m/6ft1in
Overall width	0.76m/2ft6in
Overall height(Rails up)	2.16m/7ft1in
Overall height(Rails down)	1.84m/6ft
Platform size	1.67mx0.74m/5ft7inx2ft5in
Platform extension size	0.9m/2ft11in
Ground clearance(Stowed)	0.09m/4in
Ground clearance(Raised)	0.019m/0.7in
Wheelbase	1.38m/4ft6in
Turning radius(Inside)	0m
Turning radius(Outside)	1.64m/5ft4in



Drive motors	24V/0.5kw
Lifting motor	24V/3kw



Travel speed(Stowed)	5km/h 2miles/h
Travel speed(Raised)	0.8km/h 0.5miles/h
Up/Down speed	31/37sec
Wind Rated	0-12.5m/s



Batteries	4x6V/185Ah
Integrated charger	24V/30A



Gradeability	25%
Maximum working slope	1.5-3°



Tyres	Φ 305x100mm
--------------	-------------



Weight	1400kg/3086lb
---------------	---------------

Standard Equipment

- Proportional Controls
- Automatic Pothole Protection
- Self-lock Gate On Platform
- Drivable At Full Height
- Non-marking Tyres
- 2WD
- Automatic Brakes
- Emergency Lowering System
- Emergency Stop Buttons
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Sensor With Alarm
- All Motion Alarm
- Overload Sensor With Alarm
- Horn
- Hour Meter
- Safety Brackets
- Forklift Pockets
- Folding Guardrails
- Extended Platform
- Charger Protection
- AC Power To The Platform
- Flashing Beacon

Options

- Platform Work Lights
- Airline To The Platform