



 **snorkel**

S2632
S2646
S3246

Scissor Lift

- » Working height up to 10 m.
- » Proportional controls.
- » 0,9 m extension deck.
- » Tilt alarm.
- » Swing-out service trays.
- » Power line to platform (no sockets).
- » Horn.
- » Hour meter.

Slab Scissor Lifts

Specifications

	S2632E	S2646E	S3246E
Max. working height	10 m	10 m	11,8 m
Max. platform height (A)	8 m	8 m	9,75 m
Platform capacity (SWL)	227 kg	454 kg	317 kg
Platform length (stowed)	0,74 x 2,31 m	1,14 x 2,38 m	1,14 x 2,38 m
Platform length (extended)	0,74 x 3,22 m	1,14 x 3,30 m	1,14 x 3,30 m
Deck extension length (B)	0,91 m	0,91 m	0,91 m
Overall width (C)	0,81 m	1,16 m	1,16 m
Stowed length (D)	2,37 m	2,54 m	2,54 m
Stowed height (E)	2,33 m	2,36 m	2,51 m
Weight	2224 kg	2359 kg	3003 kg
Max. drive height	8 m	7,90 m	9,75 m
Max. drive speed (elevated)	0,6 km/h	0,8 km/h	0,8 km/h
Gradeability	25 %	25 %	25 %
Inside turning radius	0,25	0,25 m	0,25
Power source	4 x 6V 250 Ah batteries	4 x 6V 240 Ah batteries	4 x 6V 250 Ah batteries

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Proportional controls.
- » Ultra-tight inside turning radius.
- » Horn.
- » Tilt alarm.
- » Swing-out service trays.
- » CE approved.
- » Hour meter.
- » CE approved.
- » 0,9 m extension deck.



TURNING RADIUS

