



**MERLO**  
GROUP AUSTRALIA

## Plant Risk Assessment

Details of Plant Assessed			
<b>Plant Type:</b>	Wheeled Telescopic Handler	<b>Model Number:</b>	P40.17EE
<b>Serial Number:</b>	D0004914	<b>Chassis Number:</b>	D102184

**Document Type:**

Form

**Title:**

Plant Risk Assessment

The conducting of the plant inspection and subsequent preparation of the Plant Risk Assessment Report has been carried out to the requirements of the NATIONAL STANDARD FOR PLANT [NOHSC:1010(1994)]

**DISCLAIMER:** No responsibility for loss occasioned by any person or company acting or refraining from acting as a result of any material or advice contained in this Plant Risk Assessment Report can be accepted by Kellyapp Pty Ltd (T/A Eastman Lynch) or its Directors. This Plant Risk Assessment Report should not be construed as indicating that the plant is without risk or is compliant with commercial standards for equivalent machinery. The Report is intended to indicate the nature of hazards and controls in place for the specific plant inspected to the level of detail as required by The National Standard for Plant [NOHSC:1010(1994)].

Document Type:	Title:	Plant Risk Assessment
Form		

## Contents

Background Information .....	3
Plant Design and Construction.....	3
Plant configuration.....	4
Plant Function .....	4
Assessment Summary .....	5
Plant Risk Assessment.....	6
Appendix 1: .....	16
Appendix 2: .....	17

### Background Information

This risk assessment should be read with reference to the operator manual for the machine being operated. This assessment does not provide operating information or instructions. The purpose of this risk assessment is to identify the risks associated with this item of plant and identify risk controls that are in place on the machine. No qualitative judgements are made on the effectiveness or adequacy of these controls or any information supplied by the manufacturer.

### Plant Design and Construction

Merlo machines and systems have been designed to comply with international standards in relation to:

#### Structural Analysis

- **DIN 15018-1:** Cranes; steel structures; verification and analyses
- **DIN 15018-2:** Cranes; steel structures; principles of design and construction
- **DIN 15018-3:** Cranes; principles relating to steel structures; design of cranes on vehicles

#### Hydraulic Systems

- **DIN 20066:** Hose assemblies - Dimensions, requirements

#### Cabin Structure

- **ISO 3471:2008** - Earth-moving machinery - Roll-over protective structures - Laboratory tests and performance requirements
- **ISO 3449:2005** - Earth-moving machinery - Falling-object protective structures - Laboratory tests and performance requirements
- **CODE 4 - 2007** - OECD standard code for the official testing of protective structures on agricultural and forestry tractors

#### Stability

- **EN 1459:** Safety of industrial trucks - Self-propelled variable reach trucks

#### Noise Levels

- **2000/14/CE:** Noise Directive

Document Type:	Title:	Plant Risk Assessment
Form		

**Plant configuration**

The Panoramic range of wheeled telescopic handlers are designed with the boom located to the right of centre of the chassis. The cabin is offset to the left hand side of the chassis while the engine and transmission are located on the right side of the boom.

**Engine**

The machine is powered by a 4 cylinder, turbocharged, water cooled diesel engine.

**Transmission**

The transmission is a two speed hydrostatic gearbox with electronically controlled variable displacement pump. An inching-control pedal controls travel speed whilst allowing high engine speed for hydraulic operation. The plant has permanent four-wheel drive.

**Boom**

The boom pivots from the rear of the machine. The telescopic sections of the boom slide on low friction pads. The hydraulic extension mechanism, hydraulic hoses and electrics are contained within the boom assembly. Attachments are attached to the carriage with quick attachment fitting system controlled from the cabin by hydraulics. The Load Management System locks out the operation of the boom when the machine's longitudinal stability limits are approached. A key override system is provided to enable the load to be moved back into a safe position.

**Cabin**

The cabin conforms to ISO 3449 (FOPS Falling Object Protection System) and ISO 3471 (ROPS - Roll Over Protection System) with the protection system fully enclosed in the cabin structure to ensure the integrity of the protection at all times. The cabin is mounted on rubber blocks for vibration reduction. Entry is through a single door. Emergency exit can be made through the front or rear windows.

**Braking**

The hydrostatic transmission provides immediate braking with the release of the accelerator. A hydraulically operated disc brake is located on each of the exit shafts of the differential, inside the axle casings. The hydraulic braking system has two independent hydraulic circuits.

An independent disc parking brake is located on the main transmission shaft. The operator is able to engage the brake manually or it will automatically engage when the engine is stopped or hydraulic pressure is lost.

**Steering**

All wheel steering occurs through a hydraulic servo-assisted system with auto synchronisation. Three steering modes are able to be selected - Front wheel steer, all wheel steer and crab steer.

**Chassis**

The chassis incorporates a frame levelling and side shift mechanism which uses hydraulic rams controlled by the operator from the cabin. The frame levelling levels the frame relative to the front axles ( $\pm 10\%$ ) when operating on uneven surfaces. The side shift moves the upper part of the chassis sideways ( $\pm 340\text{mm}$ ) to move the boom across the longitudinal axis of the machine.

Stabilisers are fitted to the front axle to provide greater stability when lifting loads.

**Plant Function**

The operator sits in a forward facing position with the load carriage to the front of him.

Steering is via a conventional steering wheel. Forward and reverse and gear selection is via switches and levers on the steering assembly. Speed and brake controls are through foot pedals. The boom control is via a right mounted joystick. The main instrument panel is forward and to the right of the operator.

Document Type:	Title:	Plant Risk Assessment
Form		

**Assessment Summary**

The purpose of this Report is to document the results of a plant inspection aimed at assessing the safety features of the design and operation of this wheeled telescopic handler.

The wheeled telescopic handler has been design to relevant standards to ensure its design, structure and operation meets the high quality required by these standards. A number of safety devices and systems are incorporated into the machine to ensure the risks to the operator and other workers are minimised during the normal operation of the machine in an appropriate work environment.

Despite the number of safety devices and systems incorporated in the machine, the safe operation of this machine is dependent on the qualification, competency and skill of the operator. Inappropriate or unskilled operation of the machine can lead to increasing the risk associated with the operation of the machine.

In addition, the work environment of the machine can present hazards to both the operator of the machine and other workers, plant and surrounding structures. The work environment must be managed in such a way as to minimise these risk.

# EASTMAN LYNCH

Safety Standard Systems Pty Ltd

ABN 40 131 718 020

## Integrated Management System

**Document Type:** Form      **Title:** Plant Risk Assessment

31 Mackenzie Street  
PO Box 933  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au



EASTMAN

ABN 40 131 718 020

Integrated Management System

Document Type: Form	Title:	Plant Risk Assessment		
		<ul style="list-style-type: none"> <li>• Low centre of gravity design</li> <li>• Frame levelling</li> <li>• Front stabilisers</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> <li>• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability</li> <li>• Cabin complies with <b>ISO 3471:2008</b> - Earth-moving machinery - Roll-over protective structures</li> </ul>	2 - b	
Poor lighting	2 - a, d, f, g	<ul style="list-style-type: none"> <li>• Driving and reversing lights on vehicle</li> <li>• Provide adequate area lighting</li> <li>• Work lights on chassis</li> <li>• Install optional lighting on cabin</li> </ul>	3	
Overhead obstacles/power	2 - a, d, f, g	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Operate in open area with overhead obstructions beyond reach of boom</li> <li>• Inching pedal allows fine control of movement</li> <li>• Side shift to place load</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> </ul>	2 - b	
Adverse weather Enclosed areas - poor ventilation	2 - a	<ul style="list-style-type: none"> <li>• Windscreen wipers - front and rear</li> <li>• Operate in open area</li> <li>• Open building doors for ventilation when operating inside</li> <li>• Provide mechanical ventilation in unventilated areas</li> </ul>	2 - b 2 - b 3	
Dusty conditions	2 - a, f	<ul style="list-style-type: none"> <li>• Air conditioned cabins</li> <li>• Ventilated work area when working inside</li> </ul>	2 - b 3	
(d) foreseeable abnormal situations, misuse and fluctuation of operating conditions;	Speeding Brake failure	<ul style="list-style-type: none"> <li>2 - f</li> <li>2 - a, c, f, g</li> </ul>	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Maintain machine as per Manufacturer's specifications</li> <li>• Brake machine by closing throttle to use hydrostatic transmission</li> <li>• Use Parking brake</li> </ul>	<ul style="list-style-type: none"> <li>3</li> <li>2 - b 3</li> </ul>
Travelling with raised load	2 - a, c, f, g		<ul style="list-style-type: none"> <li>• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability while</li> </ul>	2 - b, d 3



Integrated Management System

Document Type:	Title:	Plant Risk Assessment		
Form				
Lowering boom when travelling	2 - a, c, f, g	<ul style="list-style-type: none"> <li>• Travelling</li> <li>• Operator training</li> <li>• Travel mode prevents boom, frame levelling and side shift hydraulic capabilities operating while travelling</li> </ul>	2 - b, d	3
Sudden stops/acceleration	2 - a, c, f	<ul style="list-style-type: none"> <li>• Operator training and supervision</li> <li>• Operator training and supervision</li> </ul>	3	3
Overloading	2 - a, c, f	<ul style="list-style-type: none"> <li>• Worksite traffic management plan</li> <li>• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability</li> </ul>	2 - b	3
Lifting people	2 - a, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• People can only be lifted in a compliant cage</li> </ul>	3	3
Carrying passengers	2 - a, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Carrying passengers is prohibited</li> </ul>	3	3
Operator thrown around/out in collision/tip over	2 - a, e, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Seat belt fitted</li> <li>• Padding on roof of cabin</li> </ul>	2 - b	3
People under load	2 - a, e, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Worksite pedestrian management plan</li> </ul>	3	3
People hit by moving load	2 - a, e, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Worksite pedestrian management plan</li> </ul>	3	3
People hit by moving plant	2 - a, e, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Worksite pedestrian management plan</li> <li>• Warning decal fitted</li> </ul>	3	3
Moving engine parts	2 - a, e, f	<ul style="list-style-type: none"> <li>• Engine is enclosed by secured cover</li> <li>• Warning decal fitted</li> </ul>	2 - b, d	3
Operator cut by broken glass	2 - a, e, f	<ul style="list-style-type: none"> <li>• All windows fitted with safety glass</li> </ul>	2 - b	3
People crushed by moving parts	2 - a, e, f	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Worksite pedestrian management plan</li> <li>• Warning decal fitted</li> </ul>	3	3

## Integrated Management System

Document Type: Form	Title:	Plant Risk Assessment	
(f) generation of hazardous conditions, due to pressurised content, electricity, noise, radiation, friction, vibration, fire, explosion, temperature, moisture, vapour, gases, dust, ice, hot or cold parts;	<p>Hydraulic fluid leaks - pressure</p> <p>Noise</p> <p>Exhaust gas</p> <p>Hot parts</p> <p>Dusty conditions</p> <p>Hot fluids - oil, coolant,</p> <p>Fumes from fuel</p> <p>Battery acid</p> <p>Electrocution</p>	<p>2 - a, f</p> <p>2 - a, d, f, g</p> <p>2 - a, f</p> <p>2 - a, f</p> <p>2 - a, f</p> <p>2 - a, d, f</p> <p>2 - a, d</p> <p>2 - a, f</p>	<ul style="list-style-type: none"> <li>Major hydraulic hoses are contained within covers, under the chassis or inside the boom</li> <li>Cabin has sound proofing installed</li> <li>Cabin is attached to chassis via rubber mounts to reduce vibration and sound transference</li> <li>Exhaust is to the rear of the cabin</li> <li>Cabin is fully enclosed and fitted with air conditioning</li> <li>Enclosed worksites should be ventilated</li> <li>Engine is enclosed by secured cover</li> <li>Warning decal fitted</li> <li>Cabin is fully enclosed and fitted with air conditioning</li> <li>Engine is enclosed by secured cover</li> <li>Follow maintenance instruction in Operators Manual</li> <li>Warning decal fitted</li> <li>Fuel tank to the rear of the cabin           <ul style="list-style-type: none"> <li>with firm fitting cap</li> <li>Fuel tank constructed from damage resistant plastic</li> </ul> </li> <li>Battery is in compartment which is enclosed by secured cover</li> <li>Cover on positive terminal of battery</li> <li>12 volt electrical system</li> </ul>
(g) failure of the <i>plant</i> resulting in the loss of contents, loss of load, unintended ejection of work pieces, explosion, fragmentation or collapse of parts;	Hydraulic failure - boom	2 - a, f	<ul style="list-style-type: none"> <li>Lock valve blocks fitted to boom hydraulics to prevent boom collapse</li> </ul>
	Hydraulic failure - steering	2 - a, f	<ul style="list-style-type: none"> <li>Steering continues to operate with extra effort required due to loss of hydraulic assistance</li> </ul>
	Attachment release from carriage	2 - a, f	<ul style="list-style-type: none"> <li>Attachment locking pin hydraulic hose is disconnected from locking pin during operation to prevent accidental release of locking pin</li> <li>Operator training</li> </ul>

# EASTMAN LYNCH

ABN 40 131 718 020

## Integrated Management System

31 Mackenzie Street  
PO Box 933  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au

Document Type: Form	Title:	Plant Risk Assessment
(h) capability of the plant to lift and move people, equipment and materials and suitability of secondary back-up system to support the load;	Structural failure - boom, chassis	2 - d, f
	Attachment detaching	2 - a, f
	Hydraulic failure	2 - a, f
	Overloaded	2 - a, c, f
(i) control systems, including guarding and communication systems;	Collision	2 - a, c, d, f, g
	Engine parts	2 - a, f
	Moving parts	
	Overloaded	
	Controls	2 - a, d, f
(j) potential for falling	Tip over	2 - a, c, d, f, g

• Maintenance of machine according to Manufacturer's instructions	3	3
• Hydraulically operated locking pin is manually controlled to detach attachment	4	3
• Locking pin hydraulic hose is detached and connected to blind connector to prevent inadvertent detachment		
• Operator training		
• Lock valves fitted to all hydraulic cylinders	2 - b	2 - b
• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability		
• Warning devices - horn and flashing light, indicators.	2 - b, d	2 - b, d
• Safety glass windows in cabin		
• Reversing beeper installed		
• Worksite traffic management plan		
• Operator training		
• Load Management System includes reversing camera as an option		
• Mirrors - left and right side		
• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability		
• Engine compartment is enclosed by secured cover	2 - b, d	2 - b, d
• Warning decal fitted	6	6
• Worksite pedestrian management plan	7	7
• Warning decal fitted	3	3
• Load Management System includes a light tower to provide communication with spotter/dogman/ other workers on when machine is reaching its lifting capability limits (green - ok, Amber- 80% of capability exceeded, Red- 100% of capability exceeded)	15	15
• All controls clearly labelled and detailed in Operator's Manual	11	11
• Controls within easy reach of operator from sitting position		
• Operator training	2 - b	2 - b

## Integrated Management System

Document Type: Form	Title:	Plant Risk Assessment	
objects and the plant to roll-over;		<ul style="list-style-type: none"> <li>Operate vehicle in accordance with owner/operator manual</li> <li>Wide machine track</li> <li>Low centre of gravity design</li> <li>Frame levelling</li> <li>Front stabilisers</li> <li>Three steering modes - 4 wheel, front wheel, crab steer allowing greater manoeuvrability</li> <li>Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability</li> <li>Cabin complies with ISO 3471:2008 - Earth-moving machinery - Roll-over protective structures</li> </ul>	3
Load falling on operator	2 - a, d, f, g	<ul style="list-style-type: none"> <li>Cabin complies with ISO 3449:2005 - Earth-moving machinery - Falling-object protective structures</li> <li>Load is never suspended directly over cab.</li> <li>Carriage load guard</li> <li>Carriage is self levelling</li> <li>Side shift to place load</li> <li>Lock valves fitted to all hydraulic cylinders in case of hydraulic failure</li> </ul>	2 - b, d 7
(k) suitability of materials used for the plant;	Tyre puncture Glass breaking Chassis/Boom failure	<ul style="list-style-type: none"> <li>Machines fitted with agricultural standard tractor tyres</li> <li>Safety glass fitted to all windows</li> </ul>	2 - b 2 - b
(l) suitability and conditions of all accessories;	Poor lighting Dusty Conditions Electrocution	<ul style="list-style-type: none"> <li>Chassis and boom constructed to DIN 15018 standard</li> <li>Machine lighting includes all lights required for road travel</li> <li>Option available for four working lights on cabin - two forward and two rear</li> <li>Cabin is fully enclosed and fitted with air conditioning</li> <li>Machine is fitted with 12 volt power system</li> <li>Positive battery terminal has plastic cover</li> <li>Manual battery isolator switch (automatic switch offered as an option)</li> <li>Cabin is fully enclosed and fitted with air conditioning</li> </ul>	2 - b 2 - b, d 7 2 - b

## Integrated Management System

Document Type: Form	Title:	Plant Risk Assessment	
(m) ergonomic needs relating to installation and use;	Reversing	2 - a, c, d, f	<ul style="list-style-type: none"> <li>• Rear window allows full vision for operator</li> <li>• Load Management System provides a reversing camera as an option</li> <li>• Mirrors - left and right side</li> </ul>
Vibration		2 - a, d, f	<ul style="list-style-type: none"> <li>• Cabin attached to chassis with rubber mounts</li> <li>• Vibration absorbing seating</li> </ul>
Operator hitting head on roof of cabin	Operator hitting head on roof of cabin	2 - a, d, f	<ul style="list-style-type: none"> <li>• Seat belt fitted</li> <li>• Padding on roof of cabin</li> </ul>
Poor posture - operator		2 - a, c, d, f	<ul style="list-style-type: none"> <li>• Steering wheel and seat are fully adjustable</li> <li>• Operator sits immediately adjacent to the boom allowing excellent vision of boom and load</li> <li>• Front section of roof of cabin has a glass window for extra overhead visibility</li> <li>• narrow pillars allow greater all round vision</li> <li>• Hand throttle and inching pedal fitted to allow operator to not use accelerator during difficult manoeuvring.</li> </ul>
Awkward posture - servicing	Weight and height lifting capability is not otherwise available	2 - a, d, f	<ul style="list-style-type: none"> <li>• Visual gauge shows hydraulic oil level</li> <li>• Engine cover lifts up to provide easy access</li> </ul>
(n) carrying out the work without the plant;		2 - a, d, f	<ul style="list-style-type: none"> <li>• This machine is able to complete the required tasks within its capability</li> </ul>
(o) location in the workplace and the impact on workplace design and layout;	Other people	2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> <li>• Safety glass windows in cabin</li> <li>• Reversing beeper installed</li> <li>• Worksite traffic management plan</li> <li>• Operator training</li> <li>• Load Management System includes reversing camera as an option</li> <li>• Mirrors - left and right side</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> <li>• Warning decal fitted</li> </ul>
Other plant		2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> </ul>

## Integrated Management System

Document Type:	Title:	Plant Risk Assessment
Form		
		<ul style="list-style-type: none"> <li>• Safety glass windows in cabin</li> <li>• Reversing beeper installed</li> <li>• Worksite traffic management plan</li> <li>• Operator training</li> <li>• Load Management System includes reversing camera as an option</li> <li>• Mirrors - left and right side</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> </ul>
Building structures	2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> <li>• Safety glass windows in cabin</li> <li>• Reversing beeper installed</li> <li>• Worksite traffic management plan</li> <li>• Operator training</li> <li>• Load Management System includes reversing camera as an option</li> <li>• Mirrors - left and right side</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> </ul>
Working surface	2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Operator training</li> <li>• Operate vehicle in accordance with owner/operator manual</li> <li>• Wide machine track</li> <li>• Low centre of gravity design</li> <li>• Frame levelling</li> <li>• Front stabilisers</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> <li>• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability</li> <li>• Cabin complies with <b>ISO 3471:2008</b> - Earth-moving machinery - Roll-over protective structures</li> </ul>
(p) suitability and stability of the plant and supports;	Tip over	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> <li>• Safety glass windows in cabin</li> </ul>
(q) presence of persons and other plant in the	Collision	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> <li>• Safety glass windows in cabin</li> </ul>

## Integrated Management System

Document Type: Form	Title: Form	Plant Risk Assessment			
vicinity;		<ul style="list-style-type: none"> <li>• Reversing beeper installed</li> <li>• Worksite traffic management plan</li> <li>• Operator training</li> <li>• Load Management System includes reversing camera as an option</li> <li>• Mirrors - left and right side</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> </ul>			
(r) potential for inadvertent movement or operation of the plant;	Load dropping  Rolling forward/back  Starting in gear	2 - a, c, d, f, g  2 - a, c, d, f, g  2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Operator training on safe load handling</li> <li>• Cabin complies with <b>ISO 3449:2005</b> - Earth-moving machinery - Falling-object protective structures</li> <li>• Load is never suspended directly over cab</li> <li>• Side shift to place load</li> <li>• Carriage load guard</li> <li>• Carriage is self levelling</li> <li>• Boom fitted with lock valve block to prevent boom falling</li> <li>• Parking brake</li> <li>• Park brake applied when operator is not on seat</li> <li>• Machine will not start unless neutral gear is selected</li> </ul>	2 - b, d  3  7	2 - b  15  2 - b  14
(s) systems of work associated with the plant;	Collision	2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Warning devices - horn and flashing light, indicators.</li> <li>• Safety glass windows in cabin</li> <li>• Reversing beeper installed</li> <li>• Worksite traffic management plan</li> <li>• Operator training</li> <li>• Load Management System includes reversing camera as an option</li> <li>• Mirrors - left and right side</li> <li>• Three steering modes - 4 wheel, front wheel, crab steer allow greater manoeuvrability</li> </ul>	2 - b  3  15	2 - b  7
	Tip over	2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>• Load Management System (LMS) provides lock out of boom hydraulics if machine reaches 100% of its lifting capability</li> <li>• Frame levelling</li> <li>• Front stabilisers</li> </ul>		

# EASTMAN LYNCH

ABN 40 131 718 020

## Integrated Management System

31 Mackenzie Street  
PO Box 933  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au

Document Type:	Title:	Plant Risk Assessment			
Form					
			<ul style="list-style-type: none"> <li>Cabin complies with <b>ISO 3471:2008 - Earth-moving machinery - Roll-over protective structures</b></li> <li>Operator training on safe load handling</li> <li>Cabin complies with <b>ISO 3449:2005 - Earth-moving machinery - Falling-object protective structures</b></li> <li>Load is never suspended directly over cab</li> <li>Side shift to place load</li> <li>Carriage load guard</li> <li>Carriage is self levelling</li> <li>Boom fitted with lock valve block to prevent boom falling</li> </ul>	2 - b	7
Falling load	2 - a, c, d, f, g		<ul style="list-style-type: none"> <li>Self cleaning foot plate grip on step</li> <li>3 hand grips to assist operator access and egress cabin</li> </ul>	2 - b	2 - b
(t) access and egress; and Falls	2 - a, c, d, f		<ul style="list-style-type: none"> <li>Front and rear windows push out for emergency escape</li> <li>Optional emergency stop button</li> </ul>	2 - b	4
Emergency situation	2 - a, c, d, f			14	3
(u) competency of operators.	Collision Inappropriate operation	2 - a, c, d, f, g 2 - a, c, d, f, g	<ul style="list-style-type: none"> <li>Operator training</li> <li>Operator training</li> </ul>	3	3
<b>Other Suggested Controls Required:</b>	Hazard: Dangerous operation of machine  Hazard: Poor lighting  Hazard: Collision	Control: Recommend that purchaser of plant have the optional Emergency Stop Button fitted to the machine  Control: Recommend that purchaser of plant have the optional extra working lights fitted to the machine  Control: Recommend that purchaser of plant have the optional reversing camera fitted to the machine			

# EASTMAN LYNCH

Safety Standard Services Pty Ltd  
ABN 40 131 718 020

31 Mackenzie Street  
PO Box 933  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au

## Integrated Management System

Document Type:	Title:
Form	Plant Risk Assessment

### Appendix 1:

*Extract from the National Standard for Plant [NOHSC:1010(1994)]:*

#### **RISK ASSESSMENT**

Clause 66.

(1) Where a *hazard* is identified under Clause 65, an assessment of *risks* associated with that *hazard* must be made.

- (2) A person carrying out a *risk assessment* under Clause 66 (1) must, as far as practicable, determine a method of assessment which adequately addresses the *hazards* identified, and includes one, or a combination of the following -
- (a) a visual inspection of the *plant* and its associated environment;
  - (b) auditing;
  - (c) testing;
  - (d) a technical or scientific evaluation;
  - (e) an analysis of injury and near-miss data;
  - (f) discussions with *designers*, *manufacturers*, *suppliers*, *importers*, employers, employees or any other relevant parties; and
  - (g) a quantitative *hazard analysis*.

# EASTMAN LYNCH

31 Mackenzie Street  
PO Box 933  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au

ABN 40 131 718 020

## Integrated Management System

Document Type:	Title:
Form	Plant Risk Assessment

### Appendix 2:

*Extract from the National Standard for Plant [NOHSC:1010(1994):*

#### **CONTROL OF RISK**

Clause 67.

(1) Where an assessment under Clause 66, identifies a requirement to control a risk to health or safety, that risk must be eliminated or, where it cannot be eliminated, minimised.

(2) To minimise the risk to health and safety, one or a combination of the following approaches must be used:

- (a) substitution of the plant by less hazardous plant;
- (b) modification of the design of the plant;
- (c) isolation of the plant; and/or
- (d) engineering controls such as guarding.

(3) Where through the application of Clause 67 (2) the risk is not minimised, appropriate administrative controls and personal protective equipment must be used.

#### **Access/Egress**

(4) There must be sufficient access and egress to:

- (a) parts of plant which require cleaning and maintenance; and
- (b) the operators workstation for normal and emergency conditions.

(5) Where access to plant is required as part of normal operation, and persons may become entrapped exposing them to increased risk due to heat, cold or lack of oxygen, then the following must be provided:

- (i) emergency lighting;
- (ii) safety doors; and
- (iii) alarm systems.

#### **Dangerous Parts**

(6) Where an assessment under Clause 66 identifies a risk of exposure to dangerous parts during operation, examination, lubrication, adjustment or maintenance, that risk must be eliminated or, where it cannot be eliminated, minimised.

#### **Guarding**

(7) Where guarding is used as a control measure, a person with the responsibility for the control of risk must ensure that any guard provided for the plant and its operation is -

- (a) a permanently fixed physical barrier where no part of a person requires access to the dangerous area during normal operation, maintenance or cleaning; or

# EASTMAN LYNCH

Specialist Manufacturing Services

ABN 40 131 718 020

Document Type:	Title:
Form	Plant Risk Assessment

## Integrated Management System

31 Mackenzie Street  
PO Box 333  
Bendigo  
VIC 3552  
PH: 03 5442 7862  
admin@eastmanlynch.com.au

- (b) an interlocked physical barrier where access to dangerous areas is required during the operating sequence; or
- (c) where a *guard* in accordance with Clauses 67 (7)(a) or 67 (7)(b) is not practicable, that it is a physical barrier securely fixed in position by means of fasteners or other suitable devices, which ensures that the *guard* cannot be altered or detached without the aid of a tool or key; or
- (d) where a *guard* in accordance with Clauses 67 (7)(a), 67 (7)(b) or 67 (7)(c) is not practicable, that *presence sensing safeguarding systems* are provided.
- (8) Where *guards* are used in accordance with Clause 67 (7), they must be:
- (a) designed and constructed to make by-passing or defeating them, whether deliberately or by accident, as difficult as is reasonably possible;
  - (b) of solid construction and securely mounted so as to resist impact and shock;
  - (c) regularly maintained; and
  - (d) designed so as not to cause a *risk* in themselves.
- (9) Where parts are designed to move at high speed and may break or disintegrate, or workpieces may be ejected, the *guarding* provided must be adequate to effectively contain the fragments or workpieces.
- (10) Where a *risk* of jamming or blockage of moving parts cannot be eliminated, specific work procedures, devices and tools must be specified to ensure the plant can be cleared in a way that minimises the *risk* to health and safety.

### Operational Controls

(11) Operational controls must be:

- (a) suitably identified on *plant* so as to indicate their nature and function;
  - (b) located so as to be readily and conveniently operated by each person using the *plant*;
  - (c) located or guarded to prevent unintentional activation;
  - (d) able to be locked into the "off" position to enable the disconnection of all motive power and forces; and
- (12) Where it is not practicable to eliminate the need for *plant* to be operated during maintenance and cleaning then operational controls which permit controlled operation must be provided.

- (13) Where *plant* is designed to be operated or attended by more than one person and more than one control is fitted, the multiple controls must be of the 'stop and lock-off' type so that the *plant* cannot be restarted after a stop control has been used unless each stop control is reset.

### Emergency Stops and Warning Devices

(14) Emergency stop devices must:

- (a) be prominent, clearly and durably marked and immediately accessible to each operator of the *plant*; and
- (b) have handles, bars or push buttons which are coloured red.
- (c) not be able to be affected by electrical or electronic circuit malfunction.

- (15) Where a *risk assessment* identifies a need to have an emergency warning device this must be installed in such a position to fulfil its intended purpose.